


PUDOL liquid system care

Polishing and cleaning agent



Range of application: Polishing and cleaning agent for all metals (stainless steel, chromium, copper, brass, nickel, silver, etc.), plastics, GRP, HPL, polyester, ceramics, porcelain, glass, enamel.

Particularly suitable for basic cleaning of anodised aluminium facades.

Especially suitable for stainless steel indoors and outdoors, in canteen kitchens, gastronomy, butchers, bakeries, dairies, breweries, car service stations, shipping companies, indoor swimming pools, etc.

For plastic and anodised aluminium window frames, stainless steel railings and coverings and chrome fittings.

Ideally suited for cleaning polyester boats.

Properties:

- Free from phosphate
- Skin- and material-friendly
- It preserves and protects from corrosion
- It prevents oxidation and tarnishing of metals
- It prevents water stains and fingerprints
- It does not bind dust on the material
- Metals receive a high-gloss finish and protection from tarnishing which improves with the frequency of application
- It does not leave any scratches or grooves
- It removes deposits of lime and rust on enamel and ceramics
- It removes deposits of nicotine, flyspeck and black streaks of heels
- Removes flash rust from stainless steel in coastal areas

Technical data:

Nature of the product	Liquid
Colour	White - yellow
pH value	approx. 9

Application:

Shake before use!

Before use, check for material compatibility in an invisible position.

The material is washed off with a wet sponge with a little cleaning agent added until the water beads (use cold water).

Then dry with a chamois leather or leather cloth. Gives a high gloss finish without polishing.

Basic cleaning of anodised aluminium facades: Apply the cleaning agent with a cloth and finish with a suitable pad.

For strong rust formation and baked-on dirt, allow the paste to act for approx. 5 minutes; then rub it off with paper.

Storage:

Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures.

In closed original trading units at room temperature it is stable for at least 24 months.

PUDOL liquid system care

Polishing and cleaning agent



Packaging unit: 1 l bottle, 12 pieces in cardboard box Art.No.: 6125 - 00100
10 l canister, 60 canisters per pallet Art.No.: 6125 - 01000
Other trading units on request.

Special information: For commercial use only.
The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.
Please, also consider the Safety Data Sheet!