AGW Car Polishing Wash

Hydrophobic agent























Area of application:

As wash preservative it is suitable for manual car washing and as drying support in carwash systems.

Properties:

- Without wax
- Silicone-free
- Water drips off
- Gloss without polishing
- Wash-leathering will not be required

Free from phosphate

Technical data:

Nature of the product	Liquid
Colour	Colourless
pH-value (concentrate)	approx. 6
pH-value (1 %)	approx. 6

Application:

Do not mix it with other shampoos.

Application	Dilution
Hand wash: Pre-clean with PUDOL Car Shampoo 4001,	
Then, rewash with AGW Car Polishing Wash: pour in 5 l of water	40 ml
Automatic carwash:	1 : 200

Do not let it dry in direct sunlight.

Storage:

Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures.

In closed original trading units at room temperature it is stable for at least 24 months.

Packaging unit:

Art.No.: 4010 - 00100 1 I bottle, 12 pieces in cardboard box Art.No.: 4010 - 01000 10 I canister, 60 canisters per pallet

Other trading units on request.

Special information:

For commercial use only.

The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.

Please, also consider the Safety Data Sheet!

