## **Wastramatic Pre-Spray Cleaner**

## Special spray cleaner







Range of application:

For cleaning of cars and tarpaulins.

For pre-spraying of vehicles that shall be cleaned in a carwash system with brushes (of all makes

in general use) for trucks and buses.

**Properties:** 

Distinctive wetting

Excellent dirt-dissolving and degreasing effect

• It generates a foam padding that optimises the sliding effect of the brushes

It supports the careful removal of dirt

Free from phosphate

**Technical data:** 

Nature of the product Liquid

Colour Slightly yellowish

pH-value (concentrate) approx. 12 pH-value (1 %) approx. 10

Application:

**Application** 

**Dilution** 

Depending on the degree of pollution

1:10 to 1:50

Spray it on the vehicle, allow it to act for 5-15 minutes, then wash it away in the carwash without

using further cleaning agents.

Do not spray on hot lacquer surfaces. Do not use it in the direct sunlight.

Storage:

Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to

high temperatures.

In closed original trading units at room temperature it is stable for at least 24 months.

Packaging unit:

10 I canister, 60 canisters per pallet Art.No.: 4022 - 01000 30 I Kanister, 16 Stück pro Palette Art.Nr.: 4022 - 03000

Other trading units on request.

Special information:

For commercial use only.

The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore

non-binding and cannot be used as a basis for liability claims against us.

Please, also consider the Safety Data Sheet!

