


Workshop cleaner Ultraclean

Workshop Floor Cleaner



Area of application: For cleaning of concrete and clinker floors in car service stations and in industrial companies. Suitable also for wall tiles and extremely polluted PVC floors. For cleaning of machines and cars, steel and alloy rims.

- Properties:**
- Foam-inhibited
 - Quickly separating
 - Separator-friendly
 - Oily and fatty pollutions are quickly penetrated by the use of special wetting agents and become water-soluble

Technical data:	Nature of the product	Liquid
	Colour	Slightly yellowish
	pH-value (concentrate)	approx. 9.5
	pH-value (1 %)	approx. 8

Application:	Application	Dilution
	For medium pollutions:	1 : 100
	In case of strong pollutions:	1 : 30
	For extreme pollutions: wet the floor with the solution and allow it to act for some minutes.	

Storage: Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures. In closed original trading units at room temperature it is stable for at least 24 months.

Packaging unit: 10 l canister, 60 canisters per pallet Art.No.: 4215 - 01000
Other trading units on request.

Special information: It meets the requirements of the ÖNORM B 5105 referring to the separation properties. For commercial use only. The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.
Please, also consider the Safety Data Sheet!