Technical Information

Oil Binder VARIO-SORB Type III R - Fine grain-

Multipurpose binder



$\overline{\mathbf{y}}$	$\overline{\mathbb{N}}$	ß	K	Ŕ
		; —	;;;	

Area of application:

For binding of oil, fat, chemicals (pre-test) and other liquids.

For absorbing and gritting of escaped oils and liquids in the road traffic, on airports, in workshops, industrial companies and refineries.

For occupational safety; it prevents personal injuries, damages to environment and property - suitable for oils and chemicals.

Properties:	 Calcinated alumina Especially high and fas Easy handling Good flowing and gritti Low-dust High anti-skid property Harmless for human all Free from hazardous s Non-toxic Not caustic Non-flammable (bound) 	ng ability nd animal substances known			
Technical data:	Nature of the product	Granulate			
	Colour	Light beige			
	Granulate size	0.6 - 1.2 mm			
	Bulk weight	440 g/l			
	1 kg binds approx.	1.0 I heating oil			
Application:	After spreading on, allow it to act for some minutes.				
	After a damage, the binder absorbs the escaped liquid, binds it, whereby the material immediately regenerates and can be reused later for several times.				
	Disposal required only if it shows dark colouration.				
Storage:	Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures.				
	In closed original trading units at room temperature it is stable for at least 24 months.				
Packaging unit:	20 kg bag, 55 pieces per p	pallet	Art.No.: 8391 - 02000		
	Other trading units on requ	lest.			
Special information:	Please, always observe the details in the safety data sheet of the substance to be absorbed! For commercial use only.				

PUDOL

Oil Binder VARIO-SORB Type III R - Fine grain-

Multipurpose binder



V2 2024-02-27/EN

The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.

Please, also consider the Safety Data Sheet!



Pudol Chemie GmbH & Co. KG Bahnhofstr. 2 57520 Niederdreisbach Deutschland Tel: +49 (0) 2743 / 9212 - 0 Fax: +49 (0) 2743 / 9212 - 71 Email: info@pudol.de Internet: www.pudol.de